



# INVISION<sup>®</sup> XT 3-D Modeler

**Versatile, fast building of high-definition three-dimensional plastic models and prototypes.**



[www.3dsystems.com](http://www.3dsystems.com)

## APPLICATIONS

- Models for:
  - Concept development
  - Design validation
  - Product Presentations
- Prototypes for form and fit analysis
- Patterns for casting or molding



InVision<sup>®</sup> XT 3-D Modeler

## FEATURES

- Fast multi-jet build speed
- Productive independent of size quantity and complexity
- Exceptional surface quality
- Outstanding part durability
- Color variety
- Melt-away supports
- Compact foot print
- Quiet operation
- Network compatible
- Easy, intuitive client software

## BENEFITS

- Ready-to-use models
- Functional to withstand rigors handling and testing
- Suitable for wide range of applications
- Hands-free post processing
- Capable of building extreme geometries
- Detailed small features and thin wall models
- Office friendly
- User friendly operation

**3D SYSTEMS CORPORATION**

**TRANSFORM YOUR PRODUCTS**

# INVISION<sup>®</sup> XT 3-D Modeler

## TECHNICAL DATA

### Technology

Product	InVision <sup>®</sup> XT 3-D Modeler, software, VisiJet <sup>®</sup> material starter kit, warranty
Technology	Multi-Jet Modeling (MJM). Thermal material application, with UV-curing
Maximum Model Size	W298 x D185 x H203 mm (W11.75 x D7.3 x H8 in) (xyz)
Resolution	328 x 328 x 606 DPI (xyz)
Modeler	InVision <sup>®</sup> 3-D Modeler
Materials	Model material - VisiJet <sup>®</sup> SR 200 Support material - VisiJet <sup>®</sup> S100
Software	InVision <sup>®</sup> model client software

### Modeler

Certifications	UL certified, CE marked, CB certified
Electrical	100-127 VAC, 50/60 Hz, single-phase, 15A; 200-240* VAC, 50 Hz, single-phase, 10A; IT Power System Specification Compliant (Nordic countries)
Operating Temperature Range	18-28 °C (64-82 °F)
Noise	<65 dBA estimated (at medium fan setting)
Printer (crated) (WDH)	371 kg (817 lb)      0.96 x 1.42 x 1.67 m (38 x 56 x 66 in)
Printer (uncrated) (WDH)	254 kg (560 lb)      0.72 x 1.23 x 1.45 m (28.3 x 48.6 x 57 in)

### Interface

Network Compatibility	Network ready with 10/100 Ethernet interface
Client Hardware Recommendation (min.)	1.8 GHz Pentium IV with 512 MB RAM (with OpenGL ICD)
Client Software OS Support	Windows XP Professional/2000/NT 4.0/Me/98
Input Data File Format	.stl

### Materials

Material	Model	Support
	VisiJet <sup>®</sup> SR 200	VisiJet <sup>®</sup> S100
Composition	Acrylic plastic	n/a
Color	White, blue or gray	White
Case Quantity	8 cartridges/case	8 cartridges
Net Weight (Approximate)**	500 g (1.1 lb)	405 g (0.9 lb)
Density @ 80 °C (ASTM D4164)	1.02 g/cm <sup>3</sup>	n/a
Tensile Modulus (ASTM D638)	1772 MPa (257 KSI)	n/a
Tensile Strength (ASTM D638)	34 MPa (4.9 KSI)	n/a
Tensile Elongation at Break (ASTM D638)	7.3%	n/a
Flexural Modulus (ASTM D790)	1786 MPa (259 KSI)	n/a
Flexural Strength (ASTM D638)	52 MPa (7.5 KSI)	n/a

ASTM protocol followed for testing, except RH conditioning, which is not expected to substantially affect results.

\* Requires a small external transformer (pn 23418-901-00); supplied by 3D Systems in the country kit.

\*\* Weights and dimensions are estimated, nominal values and subject to change without notice. Accessory kit shipped separately.

Please contact:

For more information about  
3D Systems, visit us on the web at:

[www.3dsystems.com](http://www.3dsystems.com)

or contact us at

[moreinfo@3dsystems.com](mailto:moreinfo@3dsystems.com)



TRANSFORM YOUR PRODUCTS

Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use. 3D Systems makes no warranties of any type, express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.

© 2007 by 3D Systems, Inc. All rights reserved. Specifications subject to change without notice. InVision, VisiJet and the 3D logo are registered trademarks of 3D Systems, Inc.

PN 70619 Issue Date - 27 Apr 07